Peppers Cable Glands Limited

Stanhope Road, Camberley, Surrey, GU15 3BT United Kingdom

Facsimile: +44 (0) 1276 64232
Facsimile: +44 (0) 1276 691752
Fmail: sales@peppers.co.uk





Accessories:- General

Part of our Accessories Range 2008 Catalogue Page 7.4.1





A full range of accessories including locknuts, earthtags, sealing washers, serrated washers and shrouds for use with all our cable glands

AVAILABILITY						
ACCESSORY TYPE	GLAND TYPES/SIZE	THREAD TYPES				
		METRIC	NPT	BSP	PG	FRENCH
Locknuts provide a method of securing a threaded entry component into a piece of equipment						
Brass (ACBLN)	All	M16 to M100	1/2" to 4"	1/2" to 4"	PG7 to PG48	F48
316 Stainless Steel (ACSLN)	316 Stainless Steel	M16 to M100	1/2" to 4"	1/2" to 4"	PG7 to PG48	F48
Aluminium Alloy (ACALN)	Aluminium	M20 to M63	-		-	-
Nylon (ACNLN)	Nylon	M20 to M63	-	-	PG7 to PG48	-
Earth Tags provide an earth bond connection for an entry component						
Brass (ACBET)	All	M16 to M100	1/2" to 4"	1/2" to 4"	PG7 to PG48	F48
Aluminium Alloy (ACAET)	Aluminium	M20 to M63	-	-	-	-
IP Sealing Washers are fitted between an entry component and the equipment to maintain the IP rating of the equipment						
Nylon (ACNSW)	All	M16 to M100	1/2" to 4"	1/2" to 4"	PG7 to PG48	F48
Red Fibre (ACFSW)	All	M20 to M75	-	-	-	-
Serrated Star Washers can be used in conjunction with a locknut to provide additional fixing security and improve bonding						
316 Stainless Steel (ACSSW)	All	M16 to M100	1/2" to 4"	1/2" to 4"	PG7 to PG48	F48
Shrouds can be used to protect the gland from the surrounding environment						
PVC (ACSPVC)	16 to 100	Shrouds are not available for all glands, please see specific gland page for exact details				
PCP (ACSPCP)	16 to 85					
LSOH (ACSSIO)	16 to 85					

NOTES:

• As standard ISO Metric threads are supplied with a 1.5mm pitch up to and including M75 and a 2.0mm pitch for sizes above M75



Phone: +7 71133 93077; Fax: +7 71133 93074; E-Mail: info@ibemo-kz-coppers Cable Glands Limited 2008

Page 7.4.1